



Lochkreis	ET	ML-Zentrierung	Load/KG	Abrollumfang	Version	DLW-Basis Artikel
8,5x18	Uros K	tief konkav	nicht "S"			
5x108	42	60,1/63,4/65,1/67,1	735	2255	5E	USK8518425E
5x120	45	FIX 65,1	875	2100	5L1	USK8518455L1
8,5x18	Uros K	tief konkav	nur "S"			
5x108	42	60,1/63,4/65,1/67,1	735	2255	5E	USK8518425E
5x112	28	57,1/66,5/66,6	760	2200	5P2	USK8518285P2
5x112	42	57,1/66,5/66,6	850	2100	5P	USK8518425P
5x114,3	28	56,1/56,6/60,1/64,1	760	2200	5C1	USK8518285C1
		66,1/66,6/67,1/70,1				
		70,5				
5x114,3	42	56,1/56,6/60,1/64,1	850	2100	5C2	USK8518425C2
		66,1/66,6/67,1/70,1				
		70,5				
5x115	28	FIX 70,2	760	2200	5Z1	USK8518285Z1
5x120	28	FIX 72,6/72,6>67,1	825	2150	5G	USK8518285G
5x120	42	FIX 72,6/72,6>67,1	850	2100	5G2	USK8518425G2
5x120	45	FIX 65,1	875	2100	5L1	USK8518455L1
5x127	45	FIX 71,6	828	2300	5Z2	USK8518455Z2
5x130	45	FIX 71,6	828	2300	5S1	USK8518455S1
8,5x19	Manay	leicht konkav				
5x108	45	60,1/63,4/65,1/67,1	735	2255	5E	MY8519455E
5x110	35	65,1	650	2100	5F	MY8519355F
5x112	31	57,1/66,5/66,6	735	2100	5P2	MY8519315P2
5x112	33	57,1/66,5/66,6	740	2100	5B1	MY8519335B1
5x112	35	57,1/66,5/66,6	650	2100	5B	MY8519355B
5x112	35	57,1/66,5/66,6	735	2100	5B2	MY8519355B2
5x112	39	57,1/66,5/66,6	825	2255	5R	MY8519395R
5x112	45	57,1/66,5/66,6	735	2255	5P3	MY8519455P3
5x112	47	57,1/66,5/66,6	740	2255	5P4	MY8519475P4
5x112	49	57,1/66,5/66,6	735	2255	5P5	MY8519495P5
5x114,3	35	56,1/56,6/60,1/64,1	650	2100	5C	MY8519355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	39	56,1/56,6/60,1/64,1	825	2255	5C2	MY8519395C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	39	70,2/71,6	825	2255	5Z	MY8519395Z
5x120	42	64,1/65,1/67,1/72,6	825	2255	5G3	MY8519425G3
		74,1				
5x120	42	FIX 65,1	825	2255	5L1	MY8519425L1
5x130	45	FIX 71,6	825	2285	5S1	MY8519455S1
8,5x19	Uros	leicht konkav				
5x108	45	60,1/63,4/65,1/67,1	735	2255	5E	US8519455E
5x110	35	65,1	650	2100	5F	US8519355F
5x112	31	57,1/66,5/66,6	735	2100	5P2	US8519315P2

Lochkreis	ET	ML-Zentrierung	Load/KG	Abrollumfang	Version	DLW-Basis Artikel
5x112	33	57,1/66,5/66,6	740	2100	5B1	US8519335B1
5x112	35	57,1/66,5/66,6	650	2100	5B	US8519355B
5x112	35	57,1/66,5/66,6	735	2100	5B2	US8519355B2
5x112	39	57,1/66,5/66,6	825	2255	5R	US8519395R
8,5x19	Uros	leicht konkav				
5x112	45	57,1/66,5/66,6	680	2100	5P3	US8519455P3
5x112	47	57,1/66,5/66,6	685	2100	5P4	US8519475P4
5x112	49	57,1/66,5/66,6	680	2100	5P5	US8519495P5
5x114,3	39	56,1/56,6/60,1/64,1	825	2255	5C2	US8519395C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	39	70,2/71,6	825	2255	5Z	US8519395Z
5x120	42	64,1/65,1/67,1/72,6	825	2255	5G3	US8519425G3
		74,1				
5x120	42	FIX 65,1	825	2255	5L1	US8519425L1
5x130	45	FIX 71,6	800	2285	5S1	US8519455S1
8,5x19	Manay K	tief konkav				
5x105	32	56,6	620	2100	5S	MYK8519325S
5x108	35	60,1/63,4/65,1/67,1	680	2100	5E	MYK8519355E
5x112	31	57,1/66,5/66,6	680	2100	5P2	MYK8519315P2
5x112	35	57,1/66,5/66,6	680	2100	5B	MYK8519355B
5x112	40	57,1/66,5/66,6	650	2100	5R	MYK8519405R
5x112	45	57,1/66,5/66,6	600	2100	5P3	MYK8519455P3
5x114,3	35	56,1/56,6/60,1/64,1	680	2100	5C	MYK8519355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x120	18	64,1/65,1/67,1/72,6	825	2150	5N	MYK8519185N
		74,1				
5x120	25	64,1/65,1/67,1/72,6	825	2150	5G	MYK8519255G
		74,1				
5x120	35	FIX 65,1	800	2100	5L1	MYK8519355L1
5x120	38	64,1/65,1/67,1/72,6	650	2150	5G3	MYK8519385G3
		74,1				
8,5x19	Uros K	tief konkav				
5x105	32	56,6	620	2100	5S	USK8519325S
5x108	35	60,1/63,4/65,1/67,1	680	2100	5E	USK8519355E
5x112	31	57,1/66,5/66,6	680	2100	5P2	USK8519315P2
5x112	35	57,1/66,5/66,6	680	2100	5B	USK8519355B
5x112	40	57,1/66,5/66,6	650	2100	5R	USK8519405R
5x120	18	64,1/65,1/67,1/72,6	825	2150	5N	USK8519185N
		74,1				
5x120	25	64,1/65,1/67,1/72,6	825	2150	5G	USK8519255G
		74,1				
5x120	35	FIX 65,1	780	2100	5L1	USK8519355L1
5x120	38	64,1/65,1/67,1/72,6	650	2150	5G3	USK8519385G3
		74,1				
9,5x19	Manay K	tief konkav				
5x112	25	57,1/66,5/66,6	800	2285	5P2	MYK9519255P2
5x112	35	57,1/66,5/66,6	800	2285	5B	MYK9519355B

Lochkreis	ET	ML-Zentrierung	Load/KG	Abrollumfang	Version	DLW-Basis Artikel
5x112	45	57,1/66,5/66,6	825	2255	5P	MYK9519455P
5x114,3	45	56,1/56,6/60,1/64,1	825	2255	5C2	MYK9519455C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
9,5x19	Manay K	tief konkav				
5x120	25	64,1/65,1/67,1/72,6	825	2285	5G	MYK9519255G
		74,1				
5x120	38	64,1/65,1/67,1/72,6	800	2285	5G3	MYK9519385G3
		74,1				
5x130	45	FIX 71,6	825	2285	5S1	MYK9519455S1
9,5x19	Uros K	tief konkav				
5x112	25	57,1/66,5/66,6	800	2285	5P2	USK9519255P2
5x112	35	57,1/66,5/66,6	800	2285	5B	USK9519355B
5x112	45	57,1/66,5/66,6	825	2255	5P	USK9519455P
5x120	25	64,1/65,1/67,1/72,6	825	2285	5G	USK9519255G
		74,1				
5x120	38	64,1/65,1/67,1/72,6	800	2285	5G3	USK9519385G3
		74,1				
5x130	45	FIX 71,6	800	2285	5S1	USK9519455S1
11x19	Manay K	tief konkav				
5x112	42	57,1/66,5/66,6	800	2285	5B	MYK1119425B
5x130	45	FIX 71,6	700	2200	5S2	MYK1119455S2
5x130	55	FIX 71,6	700	2200	5S1	MYK1119555S1
11x19	Uros K	tief konkav				
5x112	42	57,1/66,5/66,6	800	2285	5B	USK1119425B
5x130	45	FIX 71,6	700	2200	5S2	USK1119455S2
5x130	55	FIX 71,6	700	2200	5S1	USK1119555S1
9x20	Manay	leicht konkav				
5x108	40	60,1/63,4/65,1/67,1	850	2280	5E	MY9020405E
5x112	26	57,1/66,5/66,6	850	2225	5P2	MY9020265P2
5x112	28	57,1/66,5/66,6	850	2225	5P3	MY9020285P3
5x112	35	57,1/66,5/66,6	750	2225	5B	MY9020355B
5x112	42	57,1/66,5/66,6	850	2280	5P	MY9020425P
5x114,3	28	56,1/56,6/60,1/64,1	850	2225	5C2	MY9020285C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	35	56,1/56,6/60,1/64,1	750	2225	5C	MY9020355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	42	56,1/56,6/60,1/64,1	850	2280	5C1	MY9020425C1
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x115	42	70,2/71,6	850	2280	5Z2	MY9020425Z2
5x120	35	64,1/65,1/67,1/72,6	750	2225	5G2	MY9020355G2
		74,1				
5x120	40	64,1/65,1/67,1/72,6	850	2280	5G3	MY9020405G3
		74,1				
5x120	42	FIX 65,1	850	2280	5L1	MY9020425L1

Lochkreis	ET	ML.-Zentrierung	Load/KG	Abrollumfang	Version	DLW-Basis Artikel
5x130	45	FIX 71,6	850	2310	5S2	MY9020455S2
5x130	47	FIX 71,6	850	2310	5S1	MY9020475S1
9x20 Uros leicht konkav						
5x108	40	60,1/63,4/65,1/67,1	735	2280	5E	US9020405E
5x112	26	57,1/66,5/66,6	825	2225	5P2	US9020265P2
5x112	28	57,1/66,5/66,6	825	2225	5P3	US9020285P3
5x112	35	57,1/66,5/66,6	725	2225	5B	US9020355B
5x112	42	57,1/66,5/66,6	825	2280	5P	US9020425P
5x114,3	28	56,1/56,6/60,1/64,1	825	2225	5C2	US9020285C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	35	56,1/56,6/60,1/64,1	725	2225	5C	US9020355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	42	56,1/56,6/60,1/64,1	825	2280	5C1	US9020425C1
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x115	42	70,2/71,6	825	2280	5Z2	US9020425Z2
5x120	35	64,1/65,1/67,1/72,6	725	2225	5G2	US9020355G2
		74,1				
5x120	40	64,1/65,1/67,1/72,6	825	2280	5G3	US9020405G3
		74,1				
5x120	42	FIX 65,1	825	2280	5L1	US9020425L1
5x130	45	FIX 71,6	800	2310	5S2	US9020455S2
5x130	47	FIX 71,6	800	2310	5S1	US9020475S1
9x20 Manay K tief konkav						
5x108	35	60,1/63,4/65,1/67,1	700	2150	5E	MYK9020355E
5x112	25	57,1/66,5/66,6	700	2255	5P2	MYK9020255P2
5x112	35	57,1/66,5/66,6	700	2150	5B	MYK9020355B
5x114,3	35	56,1/56,6/60,1/64,1	700	2150	5C	MYK9020355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x120	17	64,1/65,1/67,1/72,6	825	2150	5N	MYK9020175N
		74,1				
5x120	25	64,1/65,1/67,1/72,6	825	2150	5G	MYK9020255G
		74,1				
5x120	27	64,1/65,1/67,1/72,6	825	2150	5G4	MYK9020275G4
		74,1				
5x120	29	64,1/65,1/67,1/72,6	820	2150	5G5	MYK9020295G5
		74,1				
5x120	35	64,1/65,1/67,1/72,6	800	2150	5G2	MYK9020355G2
		74,1				
5x120	35	Fix 65,1	800	2150	5L1	MYK9020355L1
9x20 Uros K tief konkav						
5x108	35	60,1/63,4/65,1/67,1	680	2150	5E	USK9020355E
5x112	25	57,1/66,5/66,6	670	2255	5P2	USK9020255P2

Lochkreis	ET	ML-Zentrierung	Load/KG	Abrollumfang	Version	DLW-Basis Artikel
5x112	35	57,1/66,5/66,6	680	2150	5B	USK9020355B
5x114,3	35	56,1/56,6/60,1/64,1	680	2150	5C	USK9020355C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x120	17	64,1/65,1/67,1/72,6	825	2150	5N	USK9020175N
		74,1				
5x120	25	64,1/65,1/67,1/72,6	825	2150	5G	USK9020255G
		74,1				
5x120	27	64,1/65,1/67,1/72,6	825	2150	5G4	USK9020275G4
		74,1				
5x120	29	64,1/65,1/67,1/72,6	820	2150	5G5	USK9020295G5
		74,1				
5x120	35	64,1/65,1/67,1/72,6	680	2150	5G2	USK9020355G2
		74,1				
10,5x20 Manay K tief konkav						
5x112	30	57,1/66,5/66,6	825	2225	5P2	MYK10520305P2
5x112	40	57,1/66,5/66,6	825	2225	5B	MYK10520405B
5x114,3	38	56,1/56,6/60,1/64,1	825	2225	5C	MYK10520385C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	40	56,1/56,6/60,1/64,1	825	2225	5C1	MYK10520405C1
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x120	25	64,1/65,1/67,1/72,6	850	2310	5N	MYK10520255N
		74,1				
5x120	40	64,1/65,1/67,1/72,6	850	2310	5G3	MYK10520405G3
		74,1				
5x130	48	FIX 71,6	850	2310	5S2	MYK10520485S2
5x130	50	FIX 71,6	850	2310	5S1	MYK10520505S1
10,5x20 Uros K tief konkav						
5x112	30	57,1/66,5/66,6	780	2225	5P2	USK10520305P2
5x112	40	57,1/66,5/66,6	800	2225	5B	USK10520405B
5x114,3	30	56,1/56,6/60,1/64,1	780	2225	5C2	USK10520305C2
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	38	56,1/56,6/60,1/64,1	800	2225	5C	USK10520385C
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x114,3	40	56,1/56,6/60,1/64,1	800	2225	5C1	USK10520405C1
		66,1/66,6/67,1/68,1				
		70,1/70,5/70,6				
5x120	25	64,1/65,1/67,1/72,6	825	2310	5N	USK10520255N
		74,1				
5x120	40	64,1/65,1/67,1/72,6	825	2310	5G3	USK10520405G3
		74,1				
5x130	48	FIX 71,6	800	2310	5S2	USK10520485S2
5x130	50	FIX 71,6	800	2310	5S1	USK10520505S1